

6181Y



ÇİFT İZOLELİ TEK DAMARLI TESİSAT KABLOSU

TİP

6181Y

STANDART

BS 6004

YAPISI

- 1) İletken: BS EN 60228 Sınıf 1-2
- 2) İzole: PVC TİP T11
- 3) Kılıf: PVC TİP 6 BS 7655-4-2

KULLANIM

Kuru ve rutubetli yerlerde, sabit tesisatlarda kullanılır.

TEKNİK BİLGİLER

Maksimum Çalışma Sıcaklığı: +70°C
Anma Gerilimi: 300/500V

DOUBLE INSULATED SURFACE WIRING CABLES

TYPE

6181Y

STANDARDS

BS 6004

CONSTRUCTION

- 1) Conductor: BS EN 60228 Class 1-2
- 2) Insulation: PVC TYPE T11
- 3) Sheath: PVC TYPE 6 BS 7655-4-2

APPLICATIONS

Fixed installation in dry or damp conditions for domestic and light industrial wiring.

TECHNICAL DATA

Max.Operating Temperature: +70°C
Rated Voltage: 300/500V

NOMİNAL KESİT (mm ²)	İZOLASYON ET KALINLIĞI (mm ²)	DIŞ KILIF ET KALINLIĞI (mm)	ORTALAMA DIŞ ÇAP (mm)	SEVK UZUNLUĞU (m)	YAKLAŞIK AĞIRLIK (kg)
RATED CROSS SECTION	INSULATION THICKNESS	APPROX. OVERALL DIAMETER	APPROX. OVERALL DIAMETER	DELIVERY LENGTH	APPROX. WEIGHT
1x1	0.60	0.80	4.20	1000	28
1x1.5	0.70	0.80	4.60	1000	36
1x2.5	0.80	0.80	5.20	1000	50
1x4	0.80	0.90	6.10	1000	73
1x6	0.80	0.90	6.70	1000	96
1x10	1.00	0.90	7.90	1000	146
1x16	1.00	1.00	9.20	1000	215
1x25	1.20	1.10	10.70	1000	323
1x35	1.20	1.10	11.80	1000	417