

H05/H07VVH6-F



YASSI ASANSÖR VE DALGIÇ POMPA KABLolari

TİP

H05VVH6-F, H07VVH6-F

STANDART

CENELEC 359 TS HD 359-TS EN 50214

YAPISI

- 1) İletken: EN 60228 Sınıf 5
- 2) İzole: PVC CENELEC HD 21.1 S3 TS 9756 T12
- 3) Kılıf: PVC CENELEC HD 21.1 S3 TS 9756 TM2

KULLANIM

Asansör ve vinçlerde kontrol kablosu dalgıç dalgıç pompa kablosu olarak kullanılır.

TEKNİK BİLGİLER

Maksimum Çalışma Sıcaklığı: +70°C
Anma Gerilimi: H05VVH6-F: 300/500V
H07VVH6-F: 450/750V

FLAT LIFT AND SUBMERSIBLE PUMP CABLES

TYPE

H05VVH6-F, H07VVH6-F

STANDARDS

CENELEC 359-BS EN 50214

CONSTRUCTION

- 1) Conductor: EN 60228 Class 5
- 2) Insulation: PVC CENELEC HD 21.1 S3 T12
- 3) Sheath: PVC CENELEC HD 21.1 S3 TM2

APPLICATIONS

Specially for use in lifts, elevators cranes and submersible pumps.

TECHNICAL DATA

Max.Operating Temperature: +70°C
Rated Voltage: H05VVH6-F: 300/500V
H07VVH6-F: 450/750V

NOMİNAL KESİT (mm ²)	İZOLASYON ET KALINLIĞI (mm ²)	DIŞ KILIF ET KALINLIĞI (mm)	ORTALAMA DIŞ ÇAP (mm)	SEVK UZUNLUĞU (m)	YAKLAŞIK AĞIRLIK (kg)
RATED CROSS SECTION	INSULATION THICKNESS	APPROX. OVERALL DIAMETER	APPROX. OVERALL DIAMETER	DELIVERY LENGTH	APPROX. WEIGHT
3x0.75	0.60	0.90-1.50	4.10x9.90	1000	80
3x1	0.60	0.90-1.50	4.20x10.20	1000	88
4x0.75	0.60	0.90-1.50	4.10x12.20	1000	100
4x1	0.60	0.90-1.50	4.20x12.60	1000	111
5x0.75	0.60	0.90-1.50	4.10x14.50	1000	121
5x1	0.60	0.90-1.50	4.20x15.00	1000	134

H05/H07VVH6-F



NOMİNAL KESİT (mm ²)	İZOLASYON ET KALINLIĞI (mm)	DIŞ KILIF ET KALINLIĞI (mm)	ORTALAMA DIŞ ÇAP (mm)	SEVK UZUNLUĞU (m)	YAKLAŞIK AĞIRLIK (kg)
RATED CROSS SECTION	INSULATION THICKNESS (mm)	SHEATH THICKNESS (mm)	APPROX. OVERALL DIAMETER	DELIVERY LENGTH	APPROX. WEIGHT
3x1.5	0.70	1.00-1.50	4.90x11.70	1000	120
3x2.5	0.80	1.00-1.80	5.50x14.10	1000	171
3x4	0.80	1.20-1.80	6.50x15.90	1000	237
3x6	0.80	1.20-1.80	7.20x18.00	1000	316
3x10	1.00	1.40-1.80	8.80x21.60	1000	493
3x16	1.00	1.50-2.00	10.20x25.60	1000	721
4x1.5	0.70	1.00-1.50	4x90x14.60	1000	152
4x2.5	0.80	1.00-1.80	5.50x17.60	1000	218
4x4	0.80	1.20-1.80	6.50x20.00	1000	305
4x6	0.80	1.20-1.80	7.20x22.80	1000	408
4x10	1.00	1.40-1.80	8.80x27.60	1000	642
4x16	1.00	1.50-2.00	10.20x32.80	1000	941
5x1.5	0.70	1.00-1.50	4.90x17.50	1000	185
5x2.5	0.80	1.00-1.80	5.50x21.10	1000	264
5x4	0.80	1.20-1.80	6.50x24.10	1000	372
5x6	0.80	1.20-1.80	7.20x27.60	1000	500
5x10	1.00	1.40-1.80	8.80x33.60	1000	790
5x16	1.00	1.50-2.00	10.20x40.00	1000	1160