


N2XCY



XLPE İZOLELİ PVC KILIFLI 0.6/1 KV KONSANTRİK YER ALTI KABLOLARI

TİP

N2XCY (YXCY)

STANDART

IEC 60502-1 VDE 0276-603 TS IEC 60502-1

YAPISI

- 1) İletken: EN 60228 Sınıf 1-2
- 2) İzole: XLPE IEC 60502-1
- 3) Dolgu: PVC
- 4) Bakır iletken ve üzerini sarmal şeklinde saran bakır banttan oluşan konsantrik bakır zırh.
- 5) Kılıf: PVC, IEC 60502-1 ST1

KULLANIM

Enerji kablosu olarak endüstri, şalt yer altı tesisleri ile şehir şebekelerinde kullanılır.

TEKNİK BİLGİLER

Maksimum Çalışma Sıcaklığı: +90°C

Anma Gerilimi: 0.6/1 KV

XLPE INSULATED PVC SHEATHED ARMoured 0.6/1 KV UNDERGROUND CABLES

TYPE

N2XCY

STANDARDS

VDE 0276-603, IEC 60502-1

CONSTRUCTION

- 1) Conductor: EN 60228 Class 1-2
- 2) Insulation: XLPE IEC 60502-1
- 3) Filler: PVC
- 4) Galvanised flat steel wire armour
- 5) Galvanised steel tape armour
- 6) Sheath: PVC, IEC 60502-1 ST1

APPLICATIONS

In door installation, in ducts outdoor and underground for power stations factories, local supply systems if additional protection is necessary against contact voltage.

TECHNICAL DATA

Max.Operating Temperature: +90°C

Rated Voltage: 0.6/1 KV

NOMİNAL KESİT (mm ²)	İZOLASYON ET KALINLIĞI (mm ²)	DIŞ KILIF ET KALINLIĞI (mm)	ORTALAMA DIŞ ÇAP (mm)	SEVK UZUNLUĞU (m)	YAKLAŞIK AĞIRLIK (kg)
RATED CROSS SECTION	INSULATION THICKNESS	APPROX. OVERALL DIAMETER	APPROX. OVERALL DIAMETER	DELIVERY LENGTH	APPROX. WEIGHT
2x1.5/1.5	0.7	1.80	12.90	1000	221
2x2.5/2.5	0.7	1.80	13.30	1000	262
2x4/4	0.7	1.80	14.30	1000	324
2x6/6	0.7	1.80	15.30	1000	406
2x10/10	0.7	1.80	18.70	1000	610
2x16/16	0.7	1.80	20.90	1000	796
2x25/16	0.9	1.80	23.50	1000	1155

N2XCY



NOMİNAL KESİT (mm ²)	İZOLASYON ET KALINLIĞI (mm)	DIŞ KILIF ET KALINLIĞI (mm)	ORTALAMA DIŞ ÇAP (mm)	SEVK UZUNLUĞU (m)	YAKLAŞIK AĞIRLIK (kg)
RATED CROSS SECTION	INSULATION THICKNESS (mm)	SHEATH THICKNESS (mm)	APPROX. OVERALL DIAMETER	DELIVERY LENGTH	APPROX. WEIGHT
2x35/16	0,9	1.80	25.70	1000	1415
2x50/25	1,0	1.80	28.30	1000	1841
2x70/35	1,1	1.90	32.30	1000	2510
2x95/50	1,1	2.10	37.10	1000	3409
2x120/70	1,2	2.30	40.02	500	4166
2x150/70	1,4	2.50	44.20	500	5032
2x185/95	1,6	2.70	50.70	500	6409
2x240/120	1,7	2.80	56.50	250	8185
2x300/150	1,8	1.80	62.10	250	9978
3x1.5/1.5	0,7	1.80	13.00	1000	242
3x2.5/2.5	0,7	1.80	13.90	1000	293
3x4/4	0,7	1.80	14.90	1000	370
3x6/6	0,7	1.80	16.00	1000	469
3x10/10	0,7	1.80	19.60	1000	705
3x16/16	0,7	1.80	22.00	1000	943
3x25/16	0,9	1.80	24.80	1000	1386
3x35/16	0,9	1.90	27.20	1000	1722
3x50/25	1,0	2.00	30.20	1000	2269
3x70/35	1,1	2.10	34.50	1000	3115
3x95/50	1,1	2.30	39.40	1000	4217
3x120/70	1,2	2.40	42.90	500	5181
3x150/70	1,4	2.60	47.20	500	6311
3x185/95	1,6	2.80	54.10	500	7976
3x240/120	1,7	3.00	60.30	250	10215
3x300/150	1,8	1.80	66.50	250	12543
4x1.5/1.5	0,7	1.80	13.70	1000	272
4x2.5/2.5	0,7	1.80	14.70	1000	338
4x4/4	0,7	1.80	15.80	1000	428
4x6/6	0,7	1.80	17.00	1000	548
4x10/10	0,7	1.80	20.90	1000	831
4x16/16	0,7	1.80	23.60	1000	1133
4x25/16	0,9	1.80	26.70	1000	1677
4x35/16	0,9	1.80	29.40	1000	2107

N2XCY



NOMİNAL KESİT (mm ²)	İZOLASYON ET KALINLIĞI (mm)	DIŞ KILIF ET KALINLIĞI (mm)	ORTALAMA DIŞ ÇAP (mm)	SEVK UZUNLUĞU (m)	YAKLAŞIK AĞIRLIK (kg)
RATED CROSS SECTION	INSULATION THICKNESS (mm)	SHEATH THICKNESS (mm)	APPROX. OVERALL DIAMETER	DELIVERY LENGTH	APPROX. WEIGHT
4x50/25	1.0	2.00	32.90	1000	2792
4x70/35	1.1	2.10	37.70	1000	3864
4x95/50	1.1	2.30	43.40	500	5273
4x120/70	1.2	2.40	47.00	500	6427
4x150/70	1.4	2.60	51.90	500	7909
4x185/95	1.6	2.70	59.30	250	9921
4x240/120	1.7	3.00	66.40	250	12767
4x300/150	1.8	3.20	73.10	250	15689