


NYCY



PVC İZOLELİ PVC KILIFLI 0.6/1 KV KONSANTRİK YER ALTI KABLOLARI

TİP

YVC6V

STANDART

TS IEC 60502-1

YAPISI

- 1) İletken: EN 60228 Sınıf 1-2
- 2) İzole: PVC IEC 60502-1 PVC/A
- 3) Dolgu: PVC
- 4) Bakır konsantrik iletken
- 5) Bakır koruma bandı
- 6) Kılıf: PVC, IEC 60502-1 ST1

KULLANIM

Enerji kablosu olarak endüstri, şalt yer altı tesisleri ile şehir şebekelerinde kullanılır.

TEKNİK BİLGİLER

Maksimum Çalışma Sıcaklığı: +70°C

Anma Gerilimi: 0.6/1 KV

PVC INSULATED PVC SHEATHED ARMoured 0.6/1 KV UNDERGROUND CABLES

TYPE

NYCY

STANDARDS

VDE 0276-603, IEC 60502-1

CONSTRUCTION

- 1) Conductor: EN 60228 Class 1-2
- 2) Insulation: PVC IEC 60502-1 PVC/A
- 3) Filler: PVC
- 4) Concentric copper wire
- 5) Protective copper band
- 6) Sheath: PVC, IEC 60502-1 ST1

APPLICATIONS

In door installation, in ducts outdoor and underground for power stations factories, local supply systems if additional protection is necessary against contact voltage.

TECHNICAL DATA

Max.Operating Temperature: +70°C

Rated Voltage: 0.6/1 KV

NOMİNAL KESİT (mm ²)	İZOLASYON ET KALINLIĞI (mm ²)	DIŞ KILIF ET KALINLIĞI (mm)	ORTALAMA DIŞ ÇAP (mm)	SEVK UZUNLUĞU (m)	YAKLAŞIK AĞIRLIK (kg)
RATED CROSS SECTION	INSULATION THICKNESS	APPROX. OVERALL DIAMETER	APPROX. OVERALL DIAMETER	DELIVERY LENGTH	APPROX. WEIGHT
2x1.5/1.5	0.80	1.80	12.90	1000	239
2x2.5/2.5	0.80	1.80	13.70	1000	282
2x4/4	1.00	1.80	15.50	1000	379
2x6/6	1.00	1.80	16.50	1000	465
2x10/10	1.00	1.80	19.90	1000	678
2x16/16	1.00	1.80	22.10	1000	928
2x25/16	1.20	1.80	24.70	1000	1251

NYCY



NOMİNAL KESİT (mm ²)	İZOLASYON ET KALINLIĞI (mm)	DIŞ KILIF ET KALINLIĞI (mm)	ORTALAMA DIŞ ÇAP (mm)	SEVK UZUNLUĞU (m)	YAKLAŞIK AĞIRLIK (kg)
RATED CROSS SECTION	INSULATION THICKNESS (mm)	SHEATH THICKNESS (mm)	APPROX. OVERALL DIAMETER	DELIVERY LENGTH	APPROX. WEIGHT
2x35/16	1.20	1.80	26.90	1000	1522
2x50/25	1.40	1.80	30.10	1000	2014
2x70/35	1.40	1.90	33.70	1000	2677
2x95/50	1.60	2.00	39.10	1000	3663
2x120/70	1.60	2.10	41.80	500	4400
2x120/70	1.80	2.20	46.00	500	5331
2x150/70	2.00	2.40	52.30	500	6731
2x185/95	2.20	2.60	58.50	250	8617
2x240/120	2.40	2.70	64.70	250	10562
2x300/150	0.80	1.80	13.40	1000	264
3x1.5/1.5	0.80	1.80	14.30	1000	317
3x2.5/2.5	1.00	1.80	16.20	1000	433
3x4/4	1.00	1.80	17.30	1000	538
3x10/10	1.00	1.80	20.90	1000	786
3x16/16	1.00	1.80	23.30	1000	1090
3x25/16	1.20	1.80	26.10	1000	1502
3x35/16	1.20	1.80	28.50	1000	1852
3x50/25	1.40	1.80	31.90	1000	2447
3x70/35	1.40	2.00	36.00	1000	3321
3x95/50	1.60	2.10	41.80	1000	4549
3x120/70	1.60	2.20	44.60	500	5468
3x150/70	1.80	2.30	49.10	500	6678
3x185/95	2.00	2.50	55.80	500	8381
3x240/120	2.20	2.70	62.70	250	10792
3x300/150	2.40	2.90	69.30	250	13261
4x1.5/1.5	0.80	1.80	14.20	1000	300
4x2.5/2.5	0.80	1.80	15.10	1000	368
4x4/4	1.00	1.80	17.30	1000	506
4x6/6	1.00	1.80	18.50	1000	633
4x10/10	1.00	1.80	22.40	1000	932
4x16/16	1.00	1.80	25.00	1000	1302
4x25/16	1.20	1.80	28.20	1000	1823
4x35/16	1.20	1.80	31.00	1000	2288

NYCY



NOMİNAL KESİT (mm ²)	İZOLASYON ET KALINLIĞI (mm)	DIŞ KILIF ET KALINLIĞI (mm)	ORTALAMA DIŞ ÇAP (mm)	SEVK UZUNLUĞU (m)	YAKLAŞIK AĞIRLIK (kg)
RATED CROSS SECTION	INSULATION THICKNESS (mm)	SHEATH THICKNESS (mm)	APPROX. OVERALL DIAMETER	DELIVERY LENGTH	APPROX. WEIGHT
4x50/25	1.40	1.90	34.80	1000	3027
4x70/35	1.40	2.10	39.30	1000	4120
4x95/50	1.60	2.20	45.80	500	5659
4x120/70	1.60	2.30	49.10	500	6822
4x150/70	1.80	2.50	53.90	500	8322
4x185/95	2.00	2.70	61.40	250	10475
4x240/120	2.20	2.90	69.00	250	13495
4x300/150	2.40	3.10	76.20	250	16595