


NYFGbY



PVC İZOLELİ PVC KILIFLI ZIRHLI 0.6/1 KV YER ALTI KABLOLARI

TİP

YVZ3V

STANDART

TS IEC 60502-1

YAPISI

- 1) İletken: EN 60228 Sınıf 1-2
- 2) İzole: PVC IEC 60502-1 PVC/A
- 3) Dolgu: PVC
- 4) Yassı galvanizli çelik tel zırh
- 5) Galvanizli çelik bant
- 6) Kılıf: PVC, IEC 60502-1 ST1

KULLANIM

Üzerinde yassı galvanizli çelikten yapılmış zırh sayesinde mekanik dış tesirlere karşı çok mukavemetlidir. Ağır işletme montaj şartlarına uygundur.

TEKNİK BİLGİLER

Maksimum Çalışma Sıcaklığı: +70°C

Anma Gerilimi: 0.6/1 KV

PVC INSULATED PVC SHEATHED ARMoured 0.6/1 KV UNDERGROUND CABLES

TYPE

NYFGbY

STANDARDS

VDE 0276-603, IEC 60502-1

CONSTRUCTION

- 1) Conductor: EN 60228 Class 1-2
- 2) Insulation: PVC IEC 60502-1 PVC/A
- 3) Filler: PVC
- 4) Galvanised flat steel wire armour
- 5) Galvanised steel tape armour
- 6) Sheath: PVC, IEC 60502-1 ST1

APPLICATIONS

For installation underground, outdoor, indoor inducts and in the open where mechanical protection is required or for higher tensile stresses during installation and operation.

TECHNICAL DATA

Max.Operating Temperature: +70°C

Rated Voltage: 0.6/1 KV

NOMİNAL KESİT (mm ²)	İZOLASYON ET KALINLIĞI (mm ²)	DIŞ KILIF ET KALINLIĞI (mm)	ORTALAMA DIŞ ÇAP (mm)	SEVK UZUNLUĞU (m)	YAKLAŞIK AĞIRLIK (kg)
RATED CROSS SECTION	INSULATION THICKNESS	APPROX. OVERALL DIAMETER	APPROX. OVERALL DIAMETER	DELIVERY LENGTH	APPROX. WEIGHT
1x240	2.20	1.90	31.60	500	3127
1x300	2.40	1.90	34.00	500	3800
1x400	2.60	2.10	38.70	250	4824
1x500	2.80	2.20	43.30	250	5989
1x630	2.80	2.30	49.90	250	7604
2x10	1.00	1.80	19.70	1000	766
2x16	1.00	1.80	21.90	1000	1003

NYFGbY



NOMİNAL KESİT (mm ²)	İZOLASYON ET KALINLIĞI (mm)	DIŞ KILIF ET KALINLIĞI (mm)	ORTALAMA DIŞ ÇAP (mm)	SEVK UZUNLUĞU (m)	YAKLAŞIK AĞIRLIK (kg)
RATED CROSS SECTION	INSULATION THICKNESS (mm)	SHEATH THICKNESS (mm)	APPROX. OVERALL DIAMETER	DELIVERY LENGTH	APPROX. WEIGHT
2x25	1.20	1.80	24.50	1000	1348
2x35	1.20	1.80	26.70	1000	1640
2x50	1.40	1.80	29.70	1000	2093
2x70	1.40	1.90	33.30	1000	2712
2x95	1.60	2.10	38.90	1000	3672
2x120	1.60	2.20	41.10	1000	4243
2x150	1.80	2.30	45.10	500	5235
2x185	2.00	2.40	50.70	500	6440
2x240	2.20	2.60	56.90	250	8162
2x300	2.40	2.80	62.10	250	9920
3x10	1.00	1.80	20.70	1000	894
3x16	1.00	1.80	23.10	1000	1167
3x25	1.20	1.80	25.90	1000	1619
3x35	1.20	1.80	28.30	1000	1992
3x50	1.40	1.90	31.70	1000	2560
3x70	1.40	2.00	35.60	1000	3395
3x95	1.60	2.20	41.60	500	4583
3x120	1.60	2.30	43.90	500	5353
3x150	1.80	2.40	48.20	500	6605
3x185	2.00	2.60	54.40	250	8132
3x240	2.20	2.80	61.10	250	10359
3x300	2.40	2.90	66.50	250	12601
3x16+10	1.00/1.00	1.80	24.20	1000	1298
3x25+16	1.20/1.00	1.80	27.20	1000	1791
3x35+16	1.20/1.00	1.80	29.20	1000	2160
3x50+25	1.40/1.20	1.90	32.90	1000	2823
3x70+35	1.40/1.20	2.10	37.00	1000	3729
3x95+50	1.60/1.40	2.20	42.80	500	5037
3x120+70	1.60/1.40	2.30	45.80	500	6029
3x150+70	1.80/1.40	2.40	49.50	500	7191
3x185+95	2.00/1.60	2.60	56.30	500	9018
3x240+120	2.20/1.60	2.80	62.60	250	11366
3x300+150	2.40/1.80	3.00	68.50	250	13886

NYFGbY



NOMİNAL KESİT (mm ²)	İZOLASYON ET KALINLIĞI (mm)	DIŞ KILIF ET KALINLIĞI (mm)	ORTALAMA DIŞ ÇAP (mm)	SEVK UZUNLUĞU (m)	YAKLAŞIK AĞIRLIK (kg)
RATED CROSS SECTION	INSULATION THICKNESS (mm)	SHEATH THICKNESS (mm)	APPROX. OVERALL DIAMETER	DELIVERY LENGTH	APPROX. WEIGHT
4x10	1.00	1.80	22.20	1000	1061
4x16	1.00	1.80	24.80	1000	1400
4x25	1.20	1.80	28.00	1000	1963
4x35	1.20	1.90	30.80	1000	2453
4x50	1.40	2.00	34.60	1000	3183
4x70	1.40	2.10	38.90	1000	4237
4x95	1.60	2.30	45.60	500	5754
4x120	1.60	2.40	48.20	500	6749
4x150	1.80	2.60	53.20	500	8331
4x185	2.00	2.70	59.80	250	10268
4x240	2.20	3.00	67.40	250	13103
4x300	2.40	3.20	73.60	1000	16068
5x10	1.00	1.80	23.90	1000	1237
5x16	1.00	1.80	26.80	1000	1617
5x25	1.20	1.80	30.40	1000	2303
5x35	1.20	1.90	33.50	1000	2901
5x50	1.40	2.10	38.00	1000	3786
5x70	1.40	2.20	42.80	500	5028
5x95	1.60	2.40	50.20	500	6854
5x120	1.60	2.60	53.30	500	8022
5x150	1.80	2.70	58.60	250	9968
5x185	2.00	2.90	66.20	250	12272
5x240	2.20	3.20	74.60	250	15755
5x300	2.40	3.40	81.50	250	19279