

NYRY



PVC İZOLELİ PVC KILIFLI ZIRHLI 0.6/1 KV YER ALTI KABLOLARI

TİP

YVZ2V

STANDART

TS IEC 60502-1

YAPISI

- 1) İletken: EN 60228 Sınıf 1-2
- 2) İzole: PVC IEC 60502-1 PVC/A
- 3) Dolgu: PVC
- 4) Yuvarlak galvanizli çelik tel zırh
- 5) Kılıf: PVC, IEC 60502-1 ST1

KULLANIM

Üzerinde yuvarlak galvanizli çelikten yapılmış zırh sayesinde mekanik dış tesirlere karşı çok mukavemetlidir. Ağır işletme montaj şartlarına uygundur.

TEKNİK BİLGİLER

Maksimum Çalışma Sıcaklığı: +70°C

Anma Gerilimi: 0.6/1 KV

PVC INSULATED PVC SHEATHED ARMoured 0.6/1 KV UNDERGROUND CABLES

TYPE

NYRY

STANDARDS

VDE 0276-603, IEC 60502-1

CONSTRUCTION

- 1) Conductor: EN 60228 Class 1-2
- 2) Insulation: PVC IEC 60502-1 PVC/A
- 3) Filler: PVC
- 4) Galvanised round steel wire armour
- 5) Sheath: PVC, IEC 60502-1 ST1

APPLICATIONS

For installation underground, outdoor, indoor inducts and in the open where mechanical protection is required or for higher tensile stresses during installation and operation.

TECHNICAL DATA

Max.Operating Temperature: +70°C

Rated Voltage: 0.6/1 KV

NOMİNAL KESİT (mm ²)	İZOLASYON ET KALINLIĞI (mm ²)	DIŞ KILIF ET KALINLIĞI (mm)	ORTALAMA DIŞ ÇAP (mm)	SEVK UZUNLUĞU (m)	YAKLAŞIK AĞIRLIK (kg)
RATED CROSS SECTION	INSULATION THICKNESS	APPROX. OVERALL DIAMETER	APPROX. OVERALL DIAMETER	DELIVERY LENGTH	APPROX. WEIGHT
2x1.5	0.80	1.80	13.30	1000	346
2x2.5	0.80	1.80	14.10	1000	397
2x4	1.00	1.80	16.50	1000	598
2x6	1.00	1.80	17.50	1000	692
2x10	1.00	1.80	19.90	1000	904
2x16	1.00	1.80	22.10	1000	1143
3x1,5	0.80	1.80	13.80	1000	378

NYRY



NOMİNAL KESİT (mm ²)	İZOLASYON ET KALINLIĞI (mm)	DIŞ KILIF ET KALINLIĞI (mm)	ORTALAMA DIŞ ÇAP (mm)	SEVK UZUNLUĞU (m)	YAKLAŞIK AĞIRLIK (kg)
RATED CROSS SECTION	INSULATION THICKNESS (mm)	SHEATH THICKNESS (mm)	APPROX. OVERALL DIAMETER	DELIVERY LENGTH	APPROX. WEIGHT
3x2.5	0.80	1.80	14.70	1000	439
3x4	1.00	1.80	17.20	1000	667
3x6	1.00	1.80	18.30	1000	779
3x10	1.00	1.80	20.90	1000	1029
3x16	1.00	1.80	24.00	1000	1459
4x1.5	0.80	1.80	14.60	1000	426
4x2.5	0.80	1.80	16.40	1000	603
4x4	1.00	1.80	18.30	1000	165
4x6	1.00	1.80	19.50	1000	900
4x10	1.00	1.80	23.10	1000	1326
4x16	1.00	1.80	25.80	1000	1729
5x1.5	0.80	1.80	16.30	1000	581
5x2.5	1.00	1.80	17.40	1000	673
5x4	1.00	1.80	19.60	1000	869
5x6	1.00	1.80	20.90	1000	1027
5x10	1.00	1.80	24.80	1000	1537
5x16	1.00	1.80	28.20	1000	2009
7x1.5	0.80	1.80	17.20	1000	652
7x2.5	0.80	1.80	18.44	1000	773
8x1.5	0.80	1.80	18.64	1000	726
8x2.5	0.80	1.80	20.04	1000	871
9x1.5	0.80	1.80	19.74	1000	792
9x2.5	0.80	1.80	21.24	1000	949
10x1.5	0.80	1.80	20.34	1000	845
10x2.5	0.80	1.80	22.60	1000	1125
12x1.5	0.80	1.80	20.84	1000	909
12x2.5	0.80	1.80	23.20	1000	1233
14x1.5	0.80	1.80	22.30	1000	1108
14x2.5	0.80	1.80	24.10	1000	1330
16x1.5	0.80	1.80	23.20	1000	1199
16x2.5	0.80	1.80	25.10	1000	1444
19x1.5	0.80	1.80	24.10	1000	1298
19x2.5	0.80	1.80	26.10	1000	1590

NYRY



NOMİNAL KESİT (mm ²)	İZOLASYON ET KALINLIĞI (mm)	DIŞ KILIF ET KALINLIĞI (mm)	ORTALAMA DIŞ ÇAP (mm)	SEVK UZUNLUĞU (m)	YAKLAŞIK AĞIRLIK (kg)
RATED CROSS SECTION	INSULATION THICKNESS (mm)	SHEATH THICKNESS (mm)	APPROX. OVERALL DIAMETER	DELIVERY LENGTH	APPROX. WEIGHT
21x1,5	0.80	1.80	25,20	1000	1392
21x2,5	0.80	1.80	27,30	1000	1723
24x1,5	0.80	1.80	27,20	1000	1553
24x2,5	0.80	1.80	29,80	1000	1935
27x1,5	0.80	1.80	27,70	1000	1641
27x2,5	0.80	1.80	30,40	1000	2055
30x1,5	0.80	1.80	28,70	1000	1773
30x2,5	0.80	1.80	31,30	1000	2205
37x1,5	0.80	1.80	30,50	1000	2023
37x2,5	0.80	1.80	34,26	1000	2773
40x1,5	0.80	1.80	31,80	1000	2157
40x2,5	0.80	1.80	35,66	1000	2961