

## NYY-K



### PVC İZOLELİ PVC KILIFLI BÜKÜLGEN 0.6/1 KV YER ALTI KABLOLARI

#### TİP

NYY-K

#### STANDART

IEC 60502-1 VDE 0276-603 TS IEC 60502-1

#### YAPISI

- 1) İletken: EN 60228 Sınıf 5
- 2) İzole: PVC, IEC 60502-1 PVC/A
- 3) Dolgu: PVC
- 4) Kılıf: PVC, IEC 60502-1 ST1

#### KULLANIM

Enerji, şebeke ve aydınlatma kablosu olarak hariçte kablo kanallarında, hareketli ortamlarda toprak altında mekanik hasar riskinin olmadığı yerlerde kullanılır.

#### TEKNİK BİLGİLER

Maksimum Çalışma Sıcaklığı: +70°C  
Anma Gerilimi: 0.6/1 KV

### PVC INSULATED PVC SHEATHED FLEXIBLE 0.6/1 KV UNDERGROUND CABLES

#### TYPE

NYY-K

#### STANDARDS

IEC 60502-1 VDE 0276-603 TS IEC 60502-1

#### CONSTRUCTION

- 1) Conductor: EN 60228 Class 5
- 2) Insulation: PVC IEC 60502-1 PVC/A
- 3) Filler: PVC
- 4) Sheath: PVC IEC 60502-1 ST

#### APPLICATIONS

For installation indoors and outdoors as underground or in cable ducts, installation with additional protection where mechanical damage is unexpected.

#### TECHNICAL DATA

Max.Operating Temperature: +70°C  
Rated Voltage: 0.6/1 KV

NOMİNAL KESİT (mm <sup>2</sup> )	İZOLASYON ET KALINLIĞI (mm <sup>2</sup> )	DIŞ KILIF ET KALINLIĞI (mm)	ORTALAMA DIŞ ÇAP (mm)	SEVK UZUNLUĞU (m)	YAKLAŞIK AĞIRLIK (kg)
RATED CROSS SECTION	INSULATION THICKNESS	APPROX. OVERALL DIAMETER	APPROX. OVERALL DIAMETER	DELIVERY LENGTH	APPROX. WEIGHT
1x1.5	0.8	1.4	5.90	1000	55
1x2.5	0.8	1.4	6.30	1000	67
1x4	1.0	1.4	7.30	1000	93
1x6	1.0	1.4	8.00	1000	119
1x10	1.0	1.4	8.80	1000	169
1x16	1.0	1.4	10.00	1000	237
1x25	1.2	1.4	11.60	1000	342
1x35	1.2	1.4	12.50	1000	432
1x50	1.4	1.4	14.30	1000	603
1x70	1.4	1.4	16.10	1000	801
1x95	1.6	1.5	18.40	1000	1069
1x120	1.6	1.5	20.20	1000	1312
1x150	1.8	1.6	21.80	1000	1576
1x185	2.0	1.7	24.40	1000	1992
1x240	2.2	1.8	29.00	500	2544
1x300	2.4	1.9	31.60	500	3105
1x400	2.6	2.0	33.20	250	3223