

## TWIN FLEX



### AKÜ AKTARMA KABLOSU

#### TİP

TWIN FLEX

#### STANDART

KYM özel

#### YAPISI

- 1) İletken: IEC 60228, KYM özel
- 2) İzole: Flexible PVC
- 3) Kılıf: Şeffaf flexible

#### KULLANIM

Akü aktarma kablosu olarak kullanılır.

#### TEKNİK BİLGİLER

Çalışma Sıcaklığı: +70°C

Anma Gerilimi: 100 V

### TWIN FLEX / BATTERY CABLES

#### TYPE

TWIN FLEX

#### STANDARDS

KYM Special

#### CONSTRUCTION

- 1) Conductor: IEC 60228, extra flexible
- 2) Insulation: Flexible PVC
- 3) Sheath: Transparent flexible PVC

#### APPLICATIONS

Is used as the battery jumper cables.

#### TECHNICAL DATA

Operating Temperature: +70°C

Rated Voltage: 100 V

NOMİNAL KESİT (mm <sup>2</sup> )	İZOLASYON ET KALINLIĞI (mm <sup>2</sup> )	DIŞ KILIF ET KALINLIĞI (mm)	ORTALAMA DIŞ ÇAP (mm)	SEVK UZUNLUĞU (m)	YAKLAŞIK AĞIRLIK (kg)
RATED CROSS SECTION	INSULATION THICKNESS	APPROX. OVERALL DIAMETER	APPROX. OVERALL DIAMETER	DELIVERY LENGTH	APPROX. WEIGHT
2x1.5	1.00	0.50	4.70x9.80	100	64
2x2.5	1.00	0.50	5.10x10.60	100	85
2x4	1.00	0.50	5.70x11.70	100	117
2x6	1.00	0.50	6.30x12.90	1000	161
2x10	1.00	0.50	7.20x14.80	1000	240
2x16	1.00	0.50	8.40x17.20	1000	367
2x25	1.2	0.60	10.20x20.80	1000	539
2x35	1.2	0.60	11.10x22.60	1000	739
2x50	1.4	0.60	12.90x26.20	1000	993
2x70	1.4	0.60	14.70x29.80	1000	1428
2x95	1.6	0.70	17.00x34.40	1000	1851
2x120	1.6	0.70	18.80x38.00	500	2380
2x150	1.8	0.70	20.20x40.80	500	2928
2x185	2.0	0.70	22.60x45.60	500	3562
2x240	2.2	0.70	27.00x54.40	500	4708