

PVC İZOLELİ PVC KILIFLI BÜKÜLGEN KONTROL KABLARI

TİP

YY

STANDART

CENELEC HD 21.5 TS EN 50225-2-11 E Benzer

YAPISI

- 1) İletken: EN 60228 Sınıf 5
- 2) İzole: PVC CENELEC HD 21.1 S3 TS 9756 T12
- 3) Kılıf: PVC CENELEC HD 21.1 S3 TS 9756 TM2

KULLANIM

Sinyalizasyon sistemlerinde ve elektronik cihazların kumanda sistemlerinde kullanılır.

TEKNİK BİLGİLER

Maksimum Çalışma Sıcaklığı: +70°C

Anma Gerilimi: 300/500V

PVC INSULATED PVC SHEATHED FLEXIBLE CONTROL CABLES (NUMBERED CORES)

TYPE

YY

STANDARDS

CENELEC HD 21.5, BS 6500, VDE 0250

CONSTRUCTION

- 1) Conductor: EN 60228 Class 5
- 2) Insulation: PVC CENELEC HD 21.1 S3 T12
- 3) Sheath: PVC CENELEC HD 21.1 S3 TM2

APPLICATIONS

Used as connecting cable for measuring controlling or regulation in plant engineering for production and assembly lines. Suitable for fixed installation or for flexible use of light mechanical stress.

TECHNICAL DATA

Max.Operating Temperature: +70°C

Rated Voltage: 300/500V

NOMİNAL KESİT (mm ²)	İZOLASYON ET KALINLIĞI (mm ²)	DIŞ KILIF ET KALINLIĞI (mm)	ORTALAMA DIŞ ÇAP (mm)	SEVK UZUNLUĞU (m)	YAKLAŞIK AĞIRLIK (kg)
RATED CROSS SECTION	INSULATION THICKNESS	APPROX. OVERALL DIAMETER	APPROX. OVERALL DIAMETER	DELIVERY LENGTH	APPROX. WEIGHT
2x0,50	0.50	0.5	4.80	100	36
2x0,75	0.50	0.5	5.20	100	43
2x1	0.50	0.5	5.40	100	49
2x1,5	0.50	0.6	6.20	100	66
2x2,5	0.60	0.8	7.80	100	107
3x0,5	0.50	0.5	5.20	100	44
3x0,75	0.50	0.5	5.60	100	55
3x1	0.50	0.6	6.00	100	65
3x1,5	0.50	0.6	6.60	100	85
3x2,5	0.60	1	8.70	100	144
4x0,5	0.50	0.5	5.60	100	55
4x0,75	0.50	0.6	6.30	100	71
4x1	0.50	0.6	6.60	100	81
4x1,5	0.50	0.8	7.70	100	113
4x2,5	0.60	1	9.50	100	178

YY

NOMİNAL KESİT (mm ²)	İZOLASYON ET KALINLIĞI (mm)	DIŞ KILIF ET KALINLIĞI (mm)	ORTALAMA DIŞ ÇAP (mm)	SEVK UZUNLUĞU (m)	YAKLAŞIK AĞIRLIK (kg)
RATED CROSS SECTION	INSULATION THICKNESS (mm)	SHEATH THICKNESS (mm)	APPROX. OVERALL DIAMETER	DELIVERY LENGTH	APPROX. WEIGHT
5x0,5	0.50	0.6	6.40	100	67
5x0,75	0.50	0.8	7.30	100	91
5x1	0.50	0.8	7.60	100	103
5x1,5	0.50	1.0	8.80	100	142
5x2,5	0.60	1.1	10.60	100	215
7x0,5	0.50	0.8	7.30	100	88
7x0,75	0.50	0.8	7.90	100	110
7x1	0.50	0.8	8.20	100	127
7x1,5	0.50	1.0	9.50	100	175
7x2,5	0.60	1.3	11.90	100	279